

Drillhole data

Mount Polley Project, British Columbia, Canada

Reporting Criteria: Intercepts reported are downhole drill width (not true width). Gold and copper grades are reported to two significant figures. Samples are from core drilling which is HQ or NQ in diameter. Core is photographed and logged by the geology team before being cut. Half core HQ and NQ samples are prepared for assay and the remaining material is retained in the core lay down area for future reference. Each assay batch is submitted with duplicates and standards to monitor laboratory quality. Total depth (end of hole) is rounded to one decimal place for reporting purposes.

Hole ID	Hole Type	Easting (m)	Northing (m)	RL (m)	Total Depth (m)	Azimuth	Dip	From (m)	To (m)	Interval (m)	Cu (%)	Au (ppm)
TZ-24-04	DD	592377	5823515	1190	42	245	45	35	42	7	0.18	0.32
TZ-24-05	DD	592376	5823515	1190	321	245	45	30	65	35	0.19	0.34
								265	305	40	0.21	0.31
TZ-24-06	DD	5823474	592339	1188	306	216	48	No Significant Intercepts				
SD-24-179	DD	591690	5823230	953	513	N/A	90	22.5	492.5	470	0.47	0.39
							Incl.	22.5	292.5	270	0.65	0.48
							Incl.	195	280	85	0.71	0.88
							Incl.	195	217.5	22.5	1.29	1.69
							Incl.	257.5	280	22.5	0.83	1.02