

Mount Polley 2006 Drilling

Northeast Zone

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from	Interval to	Interval Length	Copper %	Gold g/t	Silver ppm
WB06-229	350	-70	188.1	135.0	- 148.0	13.0	0.27	0.35	1.44
WB06-230	168	-60	882.7	789.2	- 797.5	8.3	0.24	0.23	-
WB06-231	330	-45	224.0	27.5	- 35.0	7.5	0.56	0.02	-

: assay data released March 2007

Mount Polley 2006 Drilling

Southeast Zone

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from to	Interval Length	Copper %	Gold g/t	EqCu %	
SE06-55	0	-60	353.0	13.4 - 22.5	9.1	0.25	0.26	0.45	
SE06-56	90	-70	279.5	no significant intervals					
SE06-57	90	-60	320.7	190.0 - 206.7	16.7	0.09	0.49	0.48	
				218.5 - 245.0	26.5	0.17	0.21	0.34	
				288.7 - 305.5	16.8	0.15	0.37	0.44	
SE06-58	90	-70	236.8	70.0 - 97.7	27.7	0.14	0.22	0.31	
SE06-59	90	-70	209.4	22.5 - 62.5	40.0	0.12	0.22	0.29	
SE06-60	90	-70	370.9	90.0 - 115.0	25.0	0.10	0.42	0.43	
				182.5 - 202.5	20.0	0.17	0.37	0.46	
SE06-61	90	-70	309.9	190.0 - 207.5	17.5	0.17	0.40	0.48	

: assay data released March 2007

Mount Polley 2006 Drilling

Boundary Zone

Drill Hole #	Azimuth	Dip	Total Length (m)	Metre Interval from (m)	to (m)	Interval Length (m)	Copper %	Gold g/t	Silver ppm
ND06-05	0°	-90°	185.6	102.6	- 141.8	39.1	0.90	0.68	5.72
				152.7	- 172.5	19.8	0.61	0.69	3.79
ND06-06	0°	-90°	150.6	4.9	- 13.6	8.7	1.13	2.25	7.65
				40.0	- 62.5	22.5	0.37	0.40	2.86
				77.5	- 112.3	34.8	0.98	1.12	6.49
ND06-07	0°	-90°	143.0	3.1	- 15.0	11.9	0.55	2.12	3.61
				75.1	- 100.1	25.0	1.51	2.56	8.92
<i>including</i>				82.5	- 87.5	5.0	3.75	8.42	21.70
ND06-08	0°	-90°	181.7	50.0	- 102.1	52.1	0.49	0.54	3.65
				130.1	- 144.6	14.5	0.67	0.92	4.17
ND06-09	0°	-90°	384.4	46.6	- 52.8	6.2	1.02	0.55	6.87
				97.6	- 139.3	41.6	0.56	0.42	3.56
ND06-10	0°	-90°	217.9	125.0	- 145.8	20.8	0.58	0.51	-
<i>including</i>				134.6	- 145.8	11.2	0.81	0.71	-
				160.1	- 165.9	5.8	0.99	0.90	-
ND06-11	0°	-90°	267.9	no significant intervals					
ND06-12	240°	-70°	274.0	no significant intervals					
ND06-13	65°	-70°	283.2	no significant intervals					
ND06-14	0°	-90°	219.2	no significant intervals					
ND06-15	0°	-90°	276.5	90.0	- 107.5	17.5	0.79	0.91	-
ND06-16	0°	-90°	265.8	assay pending					
ND06-17	0°	-90°	266.4	155.1	- 174.5	19.4	0.68	0.50	-
<i>including</i>				158.7	- 164.9	6.2	1.55	1.05	-
ND06-18	0°	-90°	239.9	no significant interval					
ND06-19	0°	-90°	213.1	no significant interval					
ND06-20	180°	-70°	215.8	no significant interval					
ND06-21	240°	-60°	365.5	231.1	- 265.0	33.9	0.49	0.11	-
ND06-22	0°	-90°	267.3	no significant interval					
ND06-23	0°	-90°	309.7	105.0	- 112.5	7.5	1.78	1.33	-
ND06-24	0°	-90°	187.8	133.1	- 145.0	11.9	0.45	0.38	-
ND06-25	0°	-90°	172.5	no significant interval					
ND06-26	0°	-90°	429.8	262.5	- 288.0	25.5	0.83	0.60	6.48
and				325.0	- 361.2	36.2	0.28	0.13	1.48

: assay data released August 2006 through March 2007

Mount Polley 2006 Drilling

C2 Zone (1)

Drill Hole #	Azimuth	Dip	Length (m)	Metre Interval from	to	Interval Length	Copper %	Gold g/t
C206-01	0°	-90°	164.3	7.5	- 69.9	62.4	0.95	1.32
<i>including</i>				22.5	- 67.5	45.0	1.23	1.77
C206-02	0°	-90°	100.3	3.1	- 83.5	80.4	0.15	0.12
<i>including</i>				23.2	- 56.9	33.7	0.17	0.16
C206-03	0°	-90°	100.3	3.7	- 80.0	76.3	0.37	0.58
<i>including</i>				3.7	- 48.8	45.1	0.43	0.66
C206-04	0°	-90°	124.7	37.5	- 83.2	45.7	1.09	2.41
<i>and</i>				100.0	- 110.0	10.0	0.26	0.49
C206-05	270°	-55°	99.7	12.2	- 62.5	50.3	0.62	0.80
<i>including</i>				25.0	- 55.0	30.0	0.88	1.21
C206-06	0°	-90°	127.7	65.0	- 90.0	25.0	0.27	0.35
C206-07	0°	-90°	118.6	4.6	- 112.5	107.9	0.23	0.28
C206-08	270°	-55°	66.1	27.5	- 57.5	30.0	0.19	0.22
C206-09	0°	-90°	85.0	48.5	- 85.0	36.5	0.12	0.13
C206-10	270°	-60°	365.5	270	- 307.5	37.5	0.20	0.28
C206-11	270°	-60°	212.5	92.5	- 127.5	35.0	0.36	0.81
C206-12	270°	-55°	231.0	no significant intervals				
C206-13	270°	-60°	185.3	23.7	- 42.5	18.8	0.28	0.35
				102.0	- 117.5	15.5	0.25	0.37
				135.0	- 170.0	35.0	0.22	0.51
C206-14	270°	-60°	289.0	80.0	- 95.0	15.0	0.26	0.28
<i>including</i>				252.5	- 257.5	5.0	0.66	0.81
C206-15	270°	-60°	191.4	5.0	- 132.5	127.5	0.16	0.24
				155.0	- 165.0	10.0	0.22	0.48
C206-16	270°	-60°	157.9	no significant intervals				
C206-17	270°	-60°	212.8	5.0	- 30.0	25.0	0.19	0.28
C206-18	270°	-60°	168.3	8.2	- 36.5	28.3	0.21	0.21
C206-19	270°	-60°	189.6	158.2	- 179.1	20.9	0.23	0.27
C206-20	270°	-60°	212.8	7.6	- 92.5	84.9	0.28	0.33
				137.5	- 202.5	65.0	0.25	0.21
C206-21	270°	-60°	185.3	145.7	- 157.5	11.8	0.40	0.49
C206-22	270°	-60°	158.5	10.0	- 40.0	30.0	0.20	0.39
C206-23	270°	-60°	160.0	122.5	- 150.0	27.5	0.27	0.34
C206-24	270°	-60°	264.6	67.5	- 87.5	20.0	0.23	0.32
				132.5	- 165.0	32.5	0.24	0.51
				197.5	- 240.0	42.5	0.14	0.30
C206-25	270°	-60°	185.0	no significant intervals				
C206-26	270°	-60°	164.6	no significant intervals				
C206-27	270°	-60°	151.8	3.7	- 42.5	38.8	0.31	0.81

: assay data released April through August 2006

Mount Polley 2006 Drilling

C2 Zone (2)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval		Interval Length	Copper %	Gold g/t	Silver g/t	
				from	to					
C206-28	270	-60	255.4	172.5	-	252.5	80.0	0.19	0.17	-
				172.5	-	232.5	60.0	0.21	0.16	-
C206-29	270	-60	200.0	157.5	-	174.2	16.7	0.18	0.35	-
C206-30	270	-60	245.7	27.5	-	55.0	27.5	0.25	0.43	-
				122.5	-	137.5	15.0	0.25	0.15	-
				210.0	-	226.3	16.3	0.22	0.17	-
C206-31	270	-60	175.6	no significant intervals						
C206-32	270	-60	200.0	27.5	-	42.5	15.0	0.37	0.42	-
				110.7	-	122.5	11.8	0.13	0.48	-
C206-33	270	-60	233.5	187.5	-	210.0	22.5	0.23	0.22	0.14
C206-34	270	-60	151.2	110.0	-	132.5	22.5	0.15	0.23	0.00
C206-35	270	-60	200.0	5.0	-	15.0	10.0	0.22	0.21	0.32
				107.5	-	135.0	27.5	0.14	0.29	0.05
C206-36	270	-60	157.3	6.1	-	25.0	18.9	0.15	0.23	0.20
				62.5	-	70.0	7.5	0.22	0.33	0.00
				82.5	-	97.5	15.0	0.14	0.22	0.08
C206-37	270	-60	200.0	3.1	-	117.5	114.4	0.17	0.34	0.53
				3.1	-	35.0	31.9	0.23	0.33	0.82
				92.5	-	117.5	25.0	0.24	0.77	0.63
C206-38	270	-60	153.6	52.5	-	87.5	35.0	0.24	0.45	0.00
C206-39	270	-60	163.4	15.9	-	75.0	59.1	0.15	0.27	0.10
				15.9	-	42.5	26.6	0.14	0.30	0.19
				60.0	-	75.0	15.0	0.23	0.41	0.00
C206-40	270	-60	129.8	62.5	-	74.2	11.7	0.21	0.22	-
				77.9	-	95.0	17.1	0.16	0.21	-
C206-41	270	-60	102.4	42.5	-	62.5	20.0	0.15	0.24	-
C206-42	270	-60	78.4	12.5	-	66.2	53.7	0.21	0.24	-
				22.5	-	48.6	26.1	0.31	0.36	-
C206-43	270	-60	200.0	3.1	-	27.5	24.4	0.15	0.20	-
				106.1	-	200.0	93.9	0.14	0.23	-
C206-44	0	-90	87.5	30.5	-	42.5	12.0	0.34	0.51	-
C206-45	0	-90	96.6	9.9	-	37.5	27.6	0.21	0.22	-
				85.0	-	94.8	9.8	0.26	0.19	-
C206-46	270	-90	123.8	20.0	-	75.0	55.0	0.13	0.23	-
C206-47	0	-90	76.2	no significant intervals						
C206-48	330	-70	172.8	69.0	-	83.0	14.0	0.14	0.22	-
				69.0	-	147.5	78.5	0.20	0.30	-
				100.0	-	147.5	47.5	0.26	0.39	-
C206-49	270	-60	163.7	3.1	-	20.0	16.9	0.19	0.27	-
				52.5	-	112.5	60.0	0.16	0.26	-
				52.5	-	75.0	22.5	0.23	0.40	-
C206-50	270	-60	157.6	33.7	-	55.0	21.3	0.24	0.29	-
				87.5	-	102.5	15.0	0.20	0.27	-
				117.5	-	142.5	25.0	0.14	0.25	-
C206-51	270	-60	160.0	7.5	-	117.9	110.4	0.16	0.16	-
				7.5	-	33.5	26.0	0.21	0.27	-
C206-52	270	-60	169.2	no significant intervals						

: assay data released March 2007

Mount Polley 2006 Drilling

C2 Zone (3)

Drill Hole #	Azimuth (°)	Dip (°)	Length (m)	Metre Interval from	to	Interval Length	Copper %	Gold g/t	Silver g/t	
C206-53	270	-60	190.8	55.0	-	85.0	30.0	0.24	0.45	-
				122.2	-	150.0	27.8	0.18	0.27	-
				165.0	-	182.5	17.5	0.18	0.28	-
C206-54	270	-60	198.1	12.5	-	22.5	10.0	0.66	0.55	-
C206-55	270	-60	149.4	7.6	-	35.7	28.1	0.18	0.22	-
				60.0	-	130.0	70.0	0.20	0.33	-
C206-56	270	-60	163.4	37.5	-	52.5	15.0	0.28	0.34	-
				87.5	-	132.5	45.0	0.17	0.36	-
C206-57	270	-60	212.5	67.5	-	80.0	12.5	0.25	0.12	-
C206-58	270	-60	194.2	22.5	-	52.5	30.0	0.18	0.21	-
				147.5	-	177.5	30.0	0.15	0.25	-
C206-59	270	-60	221.6	no significant intervals						
C206-60	270	-60	131.4	13.7	-	87.5	73.8	0.63	0.83	-
				27.5	-	47.5	20.0	1.34	1.95	-
C206-61	270	-60	270.4	240.0	-	255.0	15.0	0.19	0.26	-
C206-62	270	-60	194.2	55.0	-	163.7	108.7	0.53	1.42	-
				100.0	-	130.0	30.0	1.03	3.01	-
				113.1	-	125.0	11.9	1.94	5.49	-
C206-63	0	-90	252.1	195.0	-	237.5	42.5	0.17	0.29	-
C206-64	270	-60	160.6	115.0	-	155.0	40.0	0.21	0.52	-
				137.5	-	150.0	12.5	0.26	0.96	-
C206-65	15	-60	264.3	102.5	-	237.5	135.0	0.24	0.36	-
C206-66	270	-60	151.9	no significant intervals						
C206-67	270	-60	215.5	no significant intervals						
C206-68	270	-60	374.0	155.0	-	182.3	27.3	0.21	0.23	-
				252.5	-	317.5	65.0	0.41	0.55	-
				366.3	-	374.0	7.7	0.32	0.55	-
				262.5	-	285.0	22.5	0.79	1.15	-
C206-69	270	-60	325.7	231.4	-	320.0	88.6	0.20	0.22	-
				290.0	-	320.0	30.0	0.27	0.37	-
C206-70	270	-60	209.4	12.2	-	127.5	115.3	0.23	0.26	-

: assay data released March 2007

Mount Polley 2006 Drilling

Bell Pit

Drill Hole #	Azimuth	Dip	Length (m)	Metre Interval from to	Interval Length	Copper %	Gold g/t
BD06-01	90°	-60°	106.1	79.2 - 106.1	26.90	0.20	0.18
BD06-02	90°	-60°	80.2	no significant intervals			
BD06-03	270°	-60°	91.4	6.1 - 91.4	85.30	0.14	0.23
BD06-04	0°	-90°	140.2	3.1 - 116.3	113.2	0.32	0.59
<i>including</i>				70.0 - 116.3	46.3	0.42	0.91

: assay data released April 2006

Mount Polley 2006 Drilling

Tall Fir Zone

Drill Hole #	Azimuth	Dip	Length (m)	Metre Interval from to	Interval Length	Copper %	Gold g/t	EqCu %
TF06-01	90°	-60°	200.6	79.4 - 117.5	38.1	0.08	0.12	0.18
TF06-02	270°	-60°	206.0	92.5 - 127.5	35.0	0.15	0.17	0.28
TF06-03	90°	-60°	200.0	no significant intervals				
TF06-04	270°	-60°	200.6	110.7 - 200.0	89.3	0.05	0.13	0.15
TF06-05	270°	-60°	198.1	42.5 - 182.7	140.2	0.05	0.17	0.18

: assay data released January 2006