

## Drillhole data

### Mount Polley Project, British Columbia, Canada

Reporting Criteria: Intercepts reported are downhole drill width (not true width). Gold and copper grades are reported to two significant figures. Samples are from core drilling which is HQ or NQ in diameter. Core is photographed and logged by the geology team before being cut. Half core HQ and NQ samples are prepared for assay and the remaining material is retained in the core lay down area for future reference. Each assay batch is submitted with duplicates and standards to monitor laboratory quality. Total depth (end of hole) is rounded to one decimal place for reporting purposes.

Hole ID	Hole Type	Easting (m)	Northing (m)	RL (m)	Total Depth (m)	Azimuth	Dip	From (m)	To (m)	Interval (m)	Cu (%)	Au (ppm)
C2-25-116	DD	592238	5822560	1026	219	270	-60	165	200	35	0.31	0.62
Including								185	200	15	0.45	1.09
C2-25-117	DD	592262	5822540	1122	213	270	-54	165	213	48	0.41	1.10
C2-25-118	DD	592248	5822463	1120	417	0	-90	290	381.2	91.2	0.53	1.10
Including	DD							347.5	381.2	33.7	0.79	2.02
C2-25-119	DD	592250	5822641	1118	246	0	-90	232.5	246.0	13.5	0.35	1.31
C2-25-120	DD	592118	5822519	1112	134	0	-90	No Significant Intercepts				
C2-25-121	DD	592250	5822505	1120	450	0	-90	282.5	435	152.5	0.46	0.97
including	DD							285	370	85	0.67	1.56