

## Drillhole data

### Mount Polley Project, British Columbia, Canada

Reporting Criteria: Intercepts reported are downhole drill width (not true width). Gold and copper grades are reported to two significant figures. Samples are from core drilling which is HQ or NQ in diameter. Core is photographed and logged by the geology team before being cut. Half core HQ and NQ samples are prepared for assay and the remaining material is retained in the core lay down area for future reference. Each assay batch is submitted with duplicates and standards to monitor laboratory quality. Total depth (end of hole) is rounded to one decimal place for reporting purposes.

Hole ID	Hole Type	Easting (m)	Northing (m)	RL (m)	Total Depth (m)	Azimuth	Dip	From (m)	To (m)	Interval (m)	Cu (%)	Au (ppm)
SD-24-178	DD	591546	5824030	1171	399.0	225	-60	30.0	42.5	12.5	0.28	0.39
and	DD							52.5	125.0	72.5	0.18	0.18
and	DD							137.5	177.5	40.0	0.18	0.14
and	DD							190.0	275.0	85.0	0.22	0.18
SD-24-180	DD	591662	5823247	955	306.0	NA	-90	35.0	292.5	257.5	0.71	0.39
Including	DD							187.5	292.5	105.0	1.13	0.58
including	DD							202.5	287.5	85.0	1.29	0.65
SD-24-181	DD	591733	5823456	928	150.0	NA	-90	42.5	65.0	22.5	0.18	0.44
and	DD							107.5	142.5	35.0	0.17	0.49