

Drillhole data

Red Chris Project, British Columbia, Canada

Reporting Criteria: Intercepts reported are downhole drill width (not true width) Au >0.1ppm (0.1g/t Au) and minimum 20m downhole width with maximum consecutive internal dilution of 10m. Also highlighted are high grade intervals of Au >0.5ppm (0.5g/t Au), Au >1ppm (1g/t Au), Au > 5ppm (5g/t Au), Au >10ppm (10g/t Au) and minimum 10m downhole width with maximum consecutive internal dilution of 10m. Gold and copper grades are reported to two significant figures. Samples are from core drilling which is HQ or NQ in diameter. Core is photographed and logged by the geology team before being cut. Half core HQ and NQ samples are prepared for assay and the remaining material is retained in the core farm for future reference. Each assay batch is submitted with duplicates and standards to monitor laboratory quality. Total depth (end of hole) is rounded to one decimal place for reporting purposes.

Hole ID	Hole Type	Easting (m)	Northing (m)	RL (m)	Total Depth (m)	Azimuth	Dip	From (m)	To (m)	Interval (m)	Au (ppm)	Cu (pct)	Cut off
RC735^M	DD	453568	6396656	1392	1501.8	147	-58	888	1128	240	0.49	0.53	0.1
							incl.	972	986	14	0.52	0.77	0.5
							incl.	1012	1114	102	0.82	0.59	0.5
							incl.	1068	1092	24	1.4	0.68	1
								1148	1170	22	0.33	0.45	0.1
								1216	1296	80	0.25	0.35	0.1
RC739^M	DD	453383	6396811	1451	1681.5	146	-57	1088	1478	390	0.63	0.48	0.1
							incl.	1244	1282	38	1.8	0.71	0.5
							incl.	1246	1268	22	2.6	1.0	1
							incl.	1302	1372	70	0.68	0.49	0.5
							incl.	1402	1446	44	2.0	1.3	0.5
							incl.	1402	1446	44	2.0	1.3	1
RC740	DD	453407	6397178	1465	2142.2	146	-45	1452	1608	156	0.73	0.71	0.1
							incl.	1522	1608	86	1.2	0.97	0.5
							incl.	1556	1602	46	1.6	1.1	1
								1738	1994	256	0.32	0.43	0.1
							incl.	1764	1864	100	0.51	0.62	0.5
RC745^M	DD	453624	6396544	1403	1364.3	145	-60	728	1094	366	0.45	0.57	0.1
							incl.	880	944	64	0.64	0.53	0.5
							incl.	958	1016	58	1.1	1.0	0.5
							incl.	960	996	36	1.4	1.2	1
RC746^M	DD	453207	6396497	1432	1043.1	150	48	110	130	20	0.11	0.01	0.1
								552	652	100	0.22	0.22	0.1
								664	716	52	0.11	0.17	0.1
								734	766	32	0.11	0.19	0.1
								956	990	34	0.15	0.02	0.1
RC747^M	DD	453548	6396527	1403	1268.2	149	-59	706	1012	306	0.28	0.39	0.1
							incl.	880	926	46	0.77	0.86	0.5
							incl.	896	916	20	1.1	1.2	1
								1094	1120	26	0.13	0.19	0.1
RC748	DD	453240	6396830	1461	1790.2	145	-60	1192	1644	452	0.60	0.54	0.1
							incl.	1224	1250	26	0.51	0.48	0.5
							incl.	1270	1330	60	0.53	0.61	0.5
							incl.	1384	1490	106	1.2	1.0	0.5
							incl.	1386	1484	98	1.3	1.0	1

